SDS 2500PG

Effective Date July 2012

1. IDENTIFICATION

Product identifier 2500 Series Part B Coating and Lining (All Colors)

Other means of identification PANSEAL Paste Grade, 2500PG

Recommended use Recommended restrictionsNot available
None known

Manufacturer/Importer/Supplier/Distributor information
Company Name: Dynesic Technologies, Inc.

15230 Surveyor Blvd., Addison, TX 75001

Phone: 972-692-0962 Phone: 972-692-0962 www.dynesic.com

Websitewww.dynesic.comEmailsphillips@dynesic.com

Emergency 24 hour telephone CHEMTREC: North America 1-800-424-9300

International 1-800-527-3887

Not classified

Not classified

Warning

Operation hours information 7:00 a.m. to 7:00 p.m.

2. HAZARD(S) IDENTIFICATION

After hours telephone number

Physical hazards Not classified Health hazards

Skin corrosion/irritation
Serious eye damage/eye irritation
Sensitization, respiratory
Sensitization, skin
Specific target organ toxicity, single exposure
Specific target organ toxicity, repeated exposure
Category 1
Category 1
Category 2
Category 2

Prevention

Wear protective gloves. Wear eye/face protection. Wash thoroughly after handling.

Environmental hazards
OSHA defined hazards
Signal word
Label elements



Response

Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

Store in accordance with local/regional/national regulations.

Disposal

Dispose of contents/container in accordance with local/regional/ national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known

HIMS ® Rating: Health: 1

Flammability: 1
Instability: 0
Personal Protection Index: C

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Chemical name	CAS number	<u>%</u>
BENZYL ALCOHOL	100-51-6	0 - 20
TRIETHYLENETETRAMINE	112-24-3	1 - 6
3-AMINOPROPYLTRIETHOXYSILANE	919-30-2	0 - 3



SDS 2500PG

Page 2.

3-AMINOPROPYLTRIETHOXYSILANE	919-30-2	0 - 3
ETHYLENEDIAMINE	107-15-3	<u>0 - 1</u>
* Other components below reportable le	evels	59.84

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation

develops and persists. Wash contaminated clothing before reuse.

4. FIRST AID MEASURES

InhalationMove to fresh air. Call a physician if symptoms develop or persist. **Skin contact**Wash off with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eve contact Rinse with water. Continue to rinse for at least 15 minutes. Get medical

attention if irritation persists after washing.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs, the head

should be kept low so that stomach vomit doesn't enter the lungs. Call

a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General Information Ensure that medical personnel are aware of the material(s) involved,

and take precautions to protect themselves.

5. FIRE-FIGHTING MEATHODS

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

5. FIRE-FIGHTING MEATHODS

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

SDS

2500PG



7. HANDLING and STORAGE

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
ETHYLENEDIAMINE (CAS 107-15-3)	PEL	25 mg/m3
US. ACGIH Threshold Limit Values		
ETHYLENEDIAMINE (CAS 107-15-3)	TWA	10 ppm
US. NIOSH: Pocket Guide to Chemical Hazards		
ETHYLENEDIAMINE (CAS 107-15-3)	TWA	25 mg/m3
		10 ppm
US. AIHA Workplace Environmental Exposure Le	vel (WEEL) Guides	
BENZYL ALCOHOL (CAS 100-51-6)	TWA	44.2 mg/m3
TRIETHYLENETETRAMINE (CAS 112-24-3)	TWA	10 ppm
		6 mg/m3
		1 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

ETHYLENEDIAMINE (CAS 107-15-3) Can be absorbed through the skin.

US WEEL Guides: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3) Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

Wear suitable protective clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene

considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Page 4.

9. PHYSICAL and CHEMICAL PROPERTIES

Paste Grade

PANSEAL

AppearanceLiquidPhysical stateLiquidFormLiquid

Color Golden to Light Amber **Odor** Ammoniacal, Amine-like

Odor threshold Not available PH Alkaline

Melting point/freezing point

Initial boiling point/boiling range
Flash point

4.64 °F (-15.2 °C) estimated
401.54 °F (205.3 °C) estimated
> 199.4 °F (> 93.0 °C) estimated

Evaporation rate Not available Flammability (solid, gas) Not available Upper/lower flammability or explosive limits

Flammability limit - lower (%) 3 % estimated
Flammability limit upper (%) 10 % estimated
Explosive limit - lower (%) Not available
Explosive limit - upper (%) Not available
Vapor pressure Not available
Vapor density Not available
Relative density Not available

Solubility(ies) Solubility (water) Partial

Partition coefficient (n-octanol/water) Not available

Auto-ignition temperature 640 °F (337.78 °C) estimated

Decomposition temperature Not available Viscosity Not available

Other information

Specific Gravity 0.95

10. STABILITY and REACTIVITY

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

IngestionExpected to be a low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact Eye contactCauses skin irritation.

Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

SDS

2500PG



Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

Specific target organ toxicity - single exposure Not classified Specific target organ toxicity - repeated exposure Not classified

Aspiration hazard Not available

Chronic effects Prolonged inhalation may be harmful.

* Estimates for product may be based on additional component data not shown. **Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization **Respiratory sensitization** Not available

Skin sensitization May cause sensitization by skin contact.

normal routes of exposure are unavailable.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified Specific target organ toxicity - repeated exposure Not classified Aspiration hazard Not available

Chronic effects Prolonged inhalation may be harmful.

12. ECOLOGICAL

<u>Product</u>	Species		Test Results
2000 Series Part B (Coating and Lir	ning (All Colors) (CAS	Mixture)
Acute			
Dermal			
LD50	Rabbit		5757.0889 mg/kg estimated
Inhalation			
LC50	Rat		2942.2148 mg/l, 8 Hours estimated
Oral			
LD50	Mouse		4648.6997 mg/kg estimated
Dermal			
LD50	Rabbit		5757.0889 mg/kg estimated
Oral			
LD50	Mouse		4648.6997 mg/kg estimated
	Rabbit		5707.897 mg/kg estimated
	Rat		3548.4497 mg/kg estimated
Other			
LD50	Mouse		2691.874 mg/kg estimated
	Rat		894.0341 mg/kg estimated
<u>Components</u>	Species		Test Results
BENZYL ALCOHOL (CAS 100-51-6))	
Acute			
Dermal			
LD50	Rabbit		2000 mg/kg
Inhalation	_		
LC50	Rat		1000 mg/l, 8 Hours
Oral			"
LD50	Mouse		1580 mg/kg
	Rabbit		1940 mg/kg
	Rat		1230 - 3100 mg/kg
Other			050 //
LD50	Mouse	5 .	950 mg/kg
		Rat	314 mg/kg



SDS 2500PG

Page 5.

<u>Components</u>	Species	Test Results
ETHYLENEDIAMINE (CAS 1 Acute	07-15-3)	
Dermal		
LD50	Rabbit	730 mg/kg
Oral LD50	Guinea pig Rat	470 mg/kg 500 mg/kg
Other		
LD50	Mouse Rat	200 mg/kg 76 mg/kg

12. ECOLOGICAL

Ecotoxicity This product contains a substance which is toxic to aquatic organisms.

<u>Product Species Test Results</u>

2000 Series Part B Coating and Lining (All Colors) (CAS Mixture)

Fish LC50 Fish 474.4284 mg/l, 96 hours estimated.

<u>Components</u> <u>Species</u> <u>Test Results</u>

BENZYL ALCOHOL (CAS 100-51-6)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) 10 mg/l, 96 hours

ETHYLENEDIAMINE (CAS 107-15-3)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas)

98.6 - 131.6 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradabilityNo data is available on the degradability of this product.

Bioaccumulative potentialNo data available.

Partition coefficient n-octanol / water (log Kow)

BENZYL ALCOHOL 1.1

ETHYLENEDIAMINE 2.04, at pH 13 **Mobility in soil** No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS

Disposal instructions

When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. PHYSICAL and CHEMICAL PROPERTIES

DOT Not regulated as dangerous goods.IATA Not regulated as dangerous goods.IMDG Not regulated as dangerous goods.

PANSEAL
Paste Grade

15. REGULATORY INFORMATION

US federal regulations

All components are on the U.S. EPA

TSCA Inventory List. TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHYLENEDIAMINE (CAS 107-15-3) Listed

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable

quantity

ETHYLENEDIAMINE (CAS 107-15-3) 5000 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name CAS number Quantity Threshold Planning quantity

ETHYLENEDIAMINE 107-15-3 5000 10000 lbs.

SARA 311/312 No

SARA 313 (TRI reporting) Not regulated

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ETHYLENEDIAMINE (CAS 107-15-3)

Safe Drinking Water Act (SDWA) Not regulated

US state regulations

US. Massachusetts RTK - Substance List

BENZYL ALCOHOL (CAS 100-51-6) ETHYLENEDIAMINE (CAS 107-15-3) TRIETHYLENETETRAMINE (CAS 112-24-3)

US. New Jersey Worker and Community Right-to-Know Act

ETHYLENEDIAMINE (CAS 107-15-3) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

BENZYL ALCOHOL (CAS 100-51-6) ETHYLENEDIAMINE (CAS 107-15-3) TRIETHYLENETETRAMINE (CAS 112-24-3)

US. Rhode Island RTK

ETHYLENEDIAMINE (CAS 107-15-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins

International Inventories

Country(s) or region/Inventory name

On inventory (yes/no)*

On miveritory (y		
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances	No
United States & P	uerto Rico Toxic Substances Control Act (TSCA) Inventory	Yes



SDS 2500PG

Page 6.

*A "Yes" indicates that all components of this product comply with the inventory requirements—administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Issue date 02-27-2023

Version # 02

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

